ļ	Ambro-Sol s.r.l.	Revision nr. 19 Dated 23/11/2016	
		Printed on 29/11/2016	
GUUI	- Grasso Multiuso	Page n. 1/13	
	Safety data sheet		
SECTION 1. Identification of the	e substance/mixture and of the compa	anv/undertaking.	
1.1. Product identifier.	C001		
Code: Product name.	G001 Grasso Multiuso		
Chemical name and synonym.	Grasso al litio chiaro		
I.3. Details of the supplier of the safety dat Name. ^F ull address. District and Country.	a sheet. Ambro-Sol s.r.l. Via per Pavone del Mella n.21 25020 Cigole (BS) Italia		
	Tel. +39 030 9959674		
	Fax. +39 030 959265		
e-mail address of the competent person.			
responsible for the Safety Data Sheet.	quality@ambro-sol.com		
1.4. Emergency telephone number. For urgent inquiries refer to.	CENTRO ANTIVELENI Ospedale Niguarda	tel: +39 02 66101029	
SECTION 2. Hazards identificat	ion.		
2.1. Classification of the substance or mixt	ure.		
ne product is classified as bazardous pursus	ant to the provisions set forth in EC Regulation 1272	2/2008 (CLP) (and subsequent amendments ar	
plements). The product thus requires a safe	ty datasheet that complies with the provisions of EC Re for health and/or the environment are given in sections	gulation 1907/2006 and subsequent amendments	

Aerosol, category 1	H222 H229	Extremely flammable aerosol. Pressurised container: may burst if heated.
Aspiration hazard, category 1	H304	May be fatal if swallowed and enters airways.
Skin irritation, category 2	H315	Causes skin irritation.
Specific target organ toxicity - single exposure, category 3	H336	May cause drowsiness or dizziness.
Hazardous to the aquatic environment, chronic toxicity, category 2	H411	Toxic to aquatic life with long lasting effects.

2.2. Label elements.

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:

	Ambro-Sol s.r.l.		Dated 23/11/2016
	G001 - Grasso Multiu	SO	Printed on 29/11/2016
			Page n. 2/13
Signal words:	Danger		
lazard statements:			
H222 H229 H315	Extremely flammable aerosol. Pressurised container: may burst if heated. Causes skin irritation.		
H336 H411	May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects.		
Precautionary statemen		.	
P210 P211 P251 P264 P273 P280 P304+P340 P410+P412	 Keep away from heat, hot surfaces, sparks, or Do not spray on an open flame or other ignition Do not pierce or burn, even after use. Wash thoroughly after handling. Avoid release to the environment. Wear protective gloves. IF INHALED: remove person to fresh air and Protect from sunlight. Do no expose to temper 	on source. keep comfortable for breathing	
Contains:	NAPHTHA (PETROLEUM), HYDROTREATE	ED LIGHT	
Statements on the aspiration toxicity classification were not included in the label elements, based on section 1.3.3. of Annex to CLP.	1		
2.3. Other hazards.			
On the basis of available	e data, the product does not contain any PBT or v	PvB in percentage greater than	0,1%.
SECTION 3. Co	mposition/information on ingredie	ents.	
3.1. Substances.			
nformation not relevant			
3.2. Mixtures.			
Contains:			
The full wording of haza	rd (H) phrases is given in section 16 of the sheet.		
Identification.	EUM), HYDROTREATED	Classification 1272/2008 (CLP).	

	Ambro-Sol s.r.l.		
GO)1 - Grasso Multiu	160	Printed on 29/11/2016
			Page n. 3/13
CAS. 64742-49-0	27 ≤ x < 31	Flam. Liq. 2 H225, Asp. Tox. 1 H304, Skin Irrit. 2 H315, STOT SE 3 H336, Aquatic Chronic 2 H411	
EC. 265-151-9			
INDEX. 649-328-00-1			
Reg. no. 012119484561-34-xxxx			
PROPANE			
CAS. 74-98-6	27 ≤ x < 31	Flam. Gas 1 H220	
EC. 200-827-9			
INDEX. 601-003-00-5			
BUTANE			
CAS. 106-97-8	11 ≤ x < 15	Flam. Gas 1 H220	
EC. 203-448-7			
INDEX. 601-004-00-0			

The product is an aerosol containing propellants. For the purposes of calculation of the health hazards, propellants are not considered (unless they have health hazards). The percentages indicated are inclusive of the propellants.

Percentage of propellants: 39,40 %

SECTION 4. First aid measures.

4.1. Description of first aid measures.

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately. INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed.

Specific information on symptoms and effects caused by the product are unknown. For symptoms and effects caused by the contained substances, see chap. 11.

4.3. Indication of any immediate medical attention and special treatment needed.

Information not available.

SECTION 5. Firefighting measures.

5.1. Extinguishing media.

SUITABLE EXTINGUISHING EQUIPMENT The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray. UNSUITABLE EXTINGUISHING EQUIPMENT None in particular.

Ambro-Soi S.r.i.	Revision nr. 19 Dated 23/11/2016
G001 - Grasso Multiuso	Printed on 29/11/2016

Page n. 4/13

5.2. Special hazards arising from the substance or mixture.

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

If overheated, aerosol cans can deform, explode and be propelled considerable distances. Put a protective helmet on before approaching the fire. Do not breathe combustion products.

5.3. Advice for firefighters.

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures.

6.1. Personal precautions, protective equipment and emergency procedures.

Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site. Send away individuals who are not suitably equipped. Wear protective gloves / protective clothing / eye protection / face protection.

6.2. Environmental precautions.

Do not disperse in the environment.

6.3. Methods and material for containment and cleaning up.

Use inert absorbent material to soak up leaked product. Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections.

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage.

7.1. Precautions for safe handling.

Avoid bunching of electrostatic charges. Do not spray on flames or incandescent bodies. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Do not eat, drink or smoke during use. Do not breathe spray.

Ambro-Sol s.r.l.	Revision nr. 19 Dated 23/11/2016
G001 - Grasso Multiuso	Printed on 29/11/2016
	Page n. 5/13

7.2. Conditions for safe storage, including any incompatibilities.

Store in a place where adequate ventilation is ensured, away from direct sunlight at a temperature below 50°C/122°F, away from any combustion sources.

7.3. Specific end use(s).

Information not available.

SECTION 8. Exposure controls/personal protection.

8.1. Control parameters.

Regulatory References:

DEU ESP	Deutschland España	MAK-und BAT-Werte-Liste 2012 INSHT - Límites de exposición profesional para agentes químicos en España 2015
FRA GBR	France United Kingdom	JORF n°0109 du 10 mai 2012 page 8773 texte n° 102 EH40/2005 Workplace exposure limits
POL	Polska	ROZPORZĄDZENIE MINISTRA PRACY I POLITYKI SPOŁECZNEJ z dnia 16 grudnia 2011r
EU	OEL EU	Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC.
	TLV-ACGIH	ACGIH 2014

NAPHTHA (PETROLEUM), HYDROTREATED LIGHT Threshold Limit Value. STEL/15min Туре Country TWA/8h mg/m3 mg/m3 ppm ppm OEL EU 72 Health - Derived no-effect level - DNEL / DMEL Effects on Effects on consumers. workers Route of exposure Acute systemic Chronic local Chronic Chronic local Chronic Acute local Acute local Acute systemic systemic systemic Oral. 1301 mg/kg/d 1301 mg/kg/d Inhalation. 1137 mg/m3 1137 mg/m3 5306 mg/m3 5306 mg/m3 Skin. 13964 13964 1377 mg/kg/d 1377 mg/kg/d mg/kg/d mg/kg/d PROPANE **Threshold Limit Value.** Country TWA/8h STEL/15min Туре ppm mg/m3 mg/m3 ppm AGW DEU 1800 7200 1000 4000 MAK DEU 1800 1000 7200 4000 NDS POL 1800 TLV-ACGIH 1000 Predicted no-effect concentration - PNEC. Normal value in fresh water NPI

NPI

Normal value in marine water

Ambro-Sol s.r.l.						vision nr. 19 ed 23/11/2016		
G001 - Grasso Multiuso					nted on 29/11/2016 je n. 6/13			
Normal value for fresh water	sediment			NPI				
Normal value for marine wat	er sediment			NPI				
Normal value for water, inter	mittent release			NPI				
Normal value of STP microo	rganisms			NPI				
Normal value for the food ch	ain (secondary poiso	ning)		NPI				
Normal value for the terrestr	ial compartment			NPI				
Normal value for the atmosp	here			NPI				
BUTANE								
Threshold Limit Value. Type	Country	TWA/8h		STEL/15min				
		mg/m3	ppm	mg/m3	ppm			
AGW	DEU	2400	1000	9600	4000			
MAK	DEU	2400	1000	9600	4000			
VLA	ESP		800					
VLEP	FRA	1900	800					
WEL	GBR	1450	600	1810	750			
NDS	POL	1900		3000				
TLV-ACGIH				2377	1000			
Predicted no-effect concentre	ation - PNEC.							
Normal value in fresh water				NPI				
Normal value in marine wate	ər			NPI				
Normal value for fresh water	sediment			NPI				
Normal value for marine wat	er sediment			NPI				
Health - Derived no-eff		DMEL						
	Effects on consumers.				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral.		NPI		NPI		NPI		NPI
Inhalation.		NPI		NPI		NPI		NPI
Skin.		NPI		NPI		NPI		NPI

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

8.2. Exposure controls.

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION None required.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap

Ambro-Sol s.r.l.

Revision nr. 19

Dated 23/11/2016 Printed on 29/11/2016

G001 - Grasso Multiuso

Page n. 7/13

and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, a mask with a type AX filter combined with a type P filter should be worn (see standard EN 14387).

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

ENVIRONMENTAL EXPOSURE CONTROLS.

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

SECTION 9. Physical and chemical properties.

9.1. Information on basic physical and chemical properties.

Appearance Colour Odour Odour threshold. pH. Melting point / freezing point. Initial boiling point. Boiling range. Flash point. Evaporation Rate Flammability of solids and gases Lower inflammability limit. Upper inflammability limit. Lower explosive limit. Upper explosive limit.	aerosol light brown characteristic of solvent Not available. Not available. Not available. < Not available. < 0 °C. Not available. flammable gas Not available. Not available. Not available. Not available.
Vapour density Relative density.	Not available. 0,630 kg/l
Solubility	Not available.
Partition coefficient: n-octanol/water Auto-ignition temperature.	Not available. Not available.
Decomposition temperature.	Not available.
Viscosity	Not available.
Explosive properties	not applicable
Oxidising properties	not applicable
9.2. Other information.	

Total solids (250°C / 482°F)	32,83 %			
VOC (Directive 2010/75/EC) :	67,17 %	-	423,17	g/litre.
VOC (volatile carbon) :	55,57 %	-	350,06	g/litre.

SECTION 10. Stability and reactivity.

10.1. Reactivity.

Ambro-Sol s.r.l.	Revision nr. 19 Dated 23/11/2016
G001 - Grasso Multiuso	Printed on 29/11/2016
	Page n. 8/13

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability.

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions.

No hazardous reactions are foreseeable in normal conditions of use and storage.

10.4. Conditions to avoid.

Avoid overheating.

10.5. Incompatible materials.

Strong reducing or oxidising agents, strong acids or alkalis, hot material.

10.6. Hazardous decomposition products.

Information not available.

SECTION 11. Toxicological information.

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification. It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on toxicological effects.

ACUTE TOXICITY.

LC50 (Inhalation - vapours) of the mixture:Not classified (no significant component).

- LC50 (Inhalation mists / powders) of the mixture:Not classified (no significant component).
- LD50 (Oral) of the mixture:Not classified (no significant component).
- LD50 (Dermal) of the mixture:Not classified (no significant component).

SKIN CORROSION / IRRITATION.

		Ambro-Sol s.r.l.	Revision nr. 19
Burner Subvision Service Subvision Service Subvision Service			
Zuses skin imitation. Serious Sev DAMAGE / IRRITATION. Dates not meet the classification criteria for this hazard class. Serious Sev DAMAGE / IRRITATION. Dates not most the classification criteria for this hazard class. Serious Sev DAMAGE / IRRITATION. Dates not meet the classification criteria for this hazard class. Serious Sev DAMAGE / IRRITATION. Dates not meet the classification criteria for this hazard class. Serious Several Se		G001 - Grasso Multiuso	
BUTANE 0,1 - 100 mg/l Rapidly biodegradable. 0,1 - 100 mg/l Rapidly bi	SERIOUS EYE DAMAGE / IRRITATIOn Does not meet the classification criter RESPIRATORY OR SKIN SENSITIS/ Does not meet the classification criter SERM CELL MUTAGENICITY. Does not meet the classification criter CARCINOGENICITY. Does not meet the classification criter REPRODUCTIVE TOXICITY. Does not meet the classification criter STOT - SINGLE EXPOSURE. May cause drowsiness or dizziness. STOT - REPEATED EXPOSURE. Does not meet the classification criter SPIRATION HAZARD. Toxic for inhalation. SECTION 12. Ecological This product is dangerous for the env 12.1. Toxicity.	ria for this hazard class. ATION. ria for this hazard class. ria for this hazard class. ria for this hazard class. ria for this hazard class. ria for this hazard class.	term, it have negative effects on acquatic environment.
apidly biodegradable. PROPANE Solubility in water. apidly biodegradable. NAPHTHA (PETROLEUM), HYDROTREATED LIGHT apidly biodegradable. 12.3. Bioaccumulative potential. BUTANE Partition coefficient: n- 1,09 ctanol/water. PROPANE Partition coefficient: n- 1,09	BUTANE		
PROPANE 0,1 - 100 mg/l Solubility in water. 0,1 - 100 mg/l Rapidly biodegradable. Image: Solubility in water. NAPHTHA (PETROLEUM), HYDROTREATED LIGHT Rapidly biodegradable. Image: Solubility in water. 12.3. Bioaccumulative potential. Image: Solubility in water. BUTANE Image: Solubility in water. PROPANE Image: Solubility in water. PROPANE Image: Solubility in water. Partition coefficient: n- octanol/water. Image: Solubility in water.		0,1 - 100 mg/i	
Solubility in water. 0,1 - 100 mg/l NAPHTHA (PETROLEUM), HYDROTREATED LIGHT tapidly biodegradable.			
Solubility in water. 0,1 - 100 mg/l NAPHTHA (PETROLEUM), HYDROTREATED LIGHT tapidly biodegradable.	PROPANE		
Rapidly biodegradable. NAPHTHA (PETROLEUM), HYDROTREATED LIGHT tapidly biodegradable. 12.3. Bioaccumulative potential. BUTANE Partition coefficient: n- 0cotanol/water. 1,09 octanol/water. 1,09 Partition coefficient: n- 1,09 Partition coefficient: n- 1,09 Partition coefficient: n- 1,09 Partition coefficient: n- 1,09 Partition coefficient: n- 1,09 Partition coefficient: n- 1,09 Partition coefficient: n- 1,09 Partition coefficient: n- 1,09 Partition coefficient: n- 1,09 Partition coefficient: n- 1,09 Partition coefficient: n- 1,09 Partition coefficient: n- 1,09 Partition coefficient: n- 1,09 Partition coefficient: n- 1,09 Partition coefficient: n- 1,09 1,09 1,09 1,09 1,09 1,09 <		0,1 - 100 mg/l	
HYDROTREATED LIGHT Rapidly biodegradable. 12.3. Bioaccumulative potential. BUTANE Partition coefficient: n- 0 octanol/water. 1,09 octanol/water. 1,09			
BUTANE Partition coefficient: n- octanol/water. PROPANE Partition coefficient: n- octanol/water.	HYDROTREATED LIGHT		
Partition coefficient: n- 1,09 octanol/water. 1,09 PROPANE 1,09 Partition coefficient: n- 1,09 octanol/water. 1,09	12.3. Bioaccumulative potential.		
Partition coefficient: n- 1,09 octanol/water. 1,09 PROPANE 1,09 Partition coefficient: n- 1,09 octanol/water. 1,09			
octanol/water. PROPANE Partition coefficient: n- 1,09 octanol/water.		1.09	
Partition coefficient: n- 1,09 octanol/water.		50,1	
octanol/water.			
12.4 Mobility in soil	PROPANE		
12.4. Mobility in soil.	Partition coefficient: n-	1,09	

Ambro-Sol s.r.l.	Revision nr. 19
AIIDI0-301 S.I.I.	
	Dated 23/11/2016
	Printed on 29/11/2016
G001 - Grasso Multiuso	111111111111111111111111111111111111111
	Dama a 40/40
	Page n. 10/13

NAPHTHA (PETROLEUM), HYDROTREATED LIGHT Partition coefficient: soil/water.

1,78

12.5. Results of PBT and vPvB assessment.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects.

Information not available.

SECTION 13. Disposal considerations.

13.1. Waste treatment methods.

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions. CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information.

14.1. UN number.

ADR / RID, IMDG, 1950 IATA:

14.2. UN proper shipping name.

ADR / RID:	AEROSOLS, FLAMMABLE
IMDG:	AEROSOLS
	(NAPHTHA (PETROLEUM),
	HYDROTREATE
	D LIGHT)
IATA:	AEROSOLS,
	FLAMMABLE

14.3. Transport hazard class(es).

ADR / RID:	Class: 2	Label: 2.1
IMDG:	Class: 2	Label: 2.1
IATA:	Class: 2	Label: 2.1



		Ambro-Sol s.r.l.		Revision nr. 19 Dated 23/11/2016
	G	001 - Grasso Multiuso		Printed on 29/11/2016 Page n. 11/13
14.4. Packing gro	oup.			•
ADR / RID, IMD(IATA:	G, -			
14.5. Environmer	ntal hazards.			
ADR / RID:	Environmentally Hazardous.			
IMDG:	Marine Pollutant.			
IATA:	NO		\checkmark	
		us mark is only mandatory for UN 3077	and UN 3082.	
14.6. Special pred	cautions for user.			
ADR / RID:		HIN - Kemler:	Limited Quantities: 1 L	Tunnel restriction code: (D)
IMDG:		Special Provision: - EMS: F-D, S-U	Limited Quantities: 1	COUS. (D)
IATA:		Cargo:	L Maximum quantity: 100	Packaging instructions:
		Pass.:	Kg Maximum quantity: 25 Kg	130 Packaging instructions: 130
		Special Instructions:	A802	150
14.7. Transport ir	n bulk according to Anr	ex II of Marpol and the IBC Code.		
Information not rel	evant.			
SECTION 1	5. Regulatory inf	ormation.		
		regulations/legislation specific for t	the substance or mixture	
	- Directive 2012/18/EC: F			
		ined substances pursuant to Annex XV	/II to EC Regulation 1907/2006	
Product.			<u> </u>	
Point.	40)		
Substances in Car	ndidate List (Art. 59 REA	<u>CH).</u>		
On the basis of av	ailable data, the product	does not contain any SVHC in percent	age greater than 0,1%.	
Substances subje	ct to authorisarion (Anne:	XIV REACH).		
None.				

Ambro-Sol s.r.l.	Revision nr. 19
	Dated 23/11/2016
G001 - Grasso Multiuso	Printed on 29/11/2016
	Page n. 12/13

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None.

Substances subject to the Rotterdam Convention:

None.

Substances subject to the Stockholm Convention:

None.

Healthcare controls.

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment.

No chemical safety assessment has been processed for the mixture and the substances it contains.

SECTION 16. Other information.

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Gas 1	Flammable gas, category 1
Aerosol 1	Aerosol, category 1
Aerosol 3	Aerosol, category 3
Flam. Liq. 2	Flammable liquid, category 2
Asp. Tox. 1	Aspiration hazard, category 1
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic toxicity, category 2
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 3
Aquatic Chronic 4	Hazardous to the aquatic environment, chronic toxicity, category 4
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H229	Pressurised container: may burst if heated.
H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)

Ambro-Sol s.r.l.	Revision nr. 19 Dated 23/11/2016
G001 - Grasso Multiuso	Printed on 29/11/2016
	Page n. 13/13
CE NUMBER: Identifier in ESIS (European archive of existing substances)	
CLP: EC Regulation 1272/2008 DNEL: Derived No Effect Level	
EmS: Emergency Schedule	
GHS: Globally Harmonized System of classification and labeling of chemicals	
IATA DGR: International Air Transport Association Dangerous Goods Regulation	
IC50: Immobilization Concentration 50% IMDG: International Maritime Code for dangerous goods	
IMO: International Maritime Organization	
INDEX NUMBER: Identifier in Annex VI of CLP	
LC50: Lethal Concentration 50%	
LD50: Lethal dose 50% OEL: Occupational Exposure Level	
PBT: Persistent bioaccumulative and toxic as REACH Regulation	
PEC: Predicted environmental Concentration	
PEL: Predicted exposure level	
PNEC: Predicted no effect concentration REACH: EC Regulation 1907/2006	
RID: Regulation concerning the international transport of dangerous goods by train	
TLV: Threshold Limit Value	
TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.	
TWA STEL: Short-term exposure limit TWA: Time-weighted average exposure limit	
VOC: Volatile organic Compounds	
vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation	
WGK: Water hazard classes (German).	
GENERAL BIBLIOGRAPHY	
 Regulation (EU) 1907/2006 (REACH) of the European Parliament Regulation (EU) 1272/2008 (CLP) of the European Parliament 	
B. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament	
I. Regulation (EU) 2015/830 of the European Parliament	
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament	
 Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament 	
B. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament	
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament	
The Merck Index 10th Edition Handling Chemical Safety	
INRS - Fiche Toxicologique (toxicological sheet)	
Patty - Industrial Hygiene and Toxicology	
N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition	
ECHA website Note for users:	
The information contained in the present sheet are based on our own knowledge on the date of the last	version. Users must verify the suitability and
horoughness of provided information according to each specific use of the product.	
This document must not be regarded as a guarantee on any specific product property. The use of this product is not subject to our direct control; therefore, users must, under their own responsib	ility comply with the current health and safety
aws and regulations. The producer is relieved from any liability arising from improper uses.	sincy, comply with the current health and salet
Provide appointed staff with adequate training on how to use chemical products.	
changes to previous review:	
The following sections were modified:)1 / 02 / 03 / 04 / 08 / 09 / 11 / 14 / 15 / 16.	
1/02/03/04/00/03/11/14/13/10.	