	CO- SPRAY S.R.L.	Revision nr. 9 Dated 22/02/2016
0004 1/201		Printed on 24/02/2016
Guu4 – Vase	eline grease 400 ml	Page n. 1/12
	Safety data sheet	
SECTION 1. Identification of the su	bstance/mixture and of the comp	any/undertaking
1.1. Product identifier		
Code:	G004	
Product name Chemical name and synonym	Grasso di vaselina grasso chiaro	
1.2. Relevant identified uses of the substance or Intended use Iubricant	r mixture and uses advised against	
1.3. Details of the supplier of the safety data she	eet	
Name	GNOCCHI ECO- SPRAY S.R.L.	
Full address District and Country	Via per Pavone del Mella sn 25020 Cigole (BS) Italia	
	Tel. +39 030 9959674	
	Fax +39 030 959265	
e-mail address of the competent person	Fax +39 030 959265	
e-mail address of the competent person responsible for the Safety Data Sheet	Fax +39 030 959265 info@gnocchiecospray.com	
responsible for the Safety Data Sheet 1.4. Emergency telephone number		tel: +39 02 66101029
e-mail address of the competent person responsible for the Safety Data Sheet <b>1.4. Emergency telephone number</b> For urgent inquiries refer to <b>SECTION 2. Hazards identification.</b>	info@gnocchiecospray.com CENTRO ANTIVELENI Ospedale Niguarda	tel: +39 02 66101029

The product is classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:		
Aerosol, category 1	H222 H229	Extremely flammable aerosol. Pressurised container: may burst if heated.
Aspiration hazard, category 1 Skin irritation, category 2 Specific target organ toxicity - single exposure, category 3 Hazardous to the aquatic environment, chronic toxicity, category 2	H304 H315 H336 H411	May be fatal if swallowed and enters airways. Causes skin irritation. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects.

## 2.2. Label elements.

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

	GNOCCHIE	CO- SPRAY	S.R.L.	Revision nr. 9 Dated 22/02/2016
	G004 – Vase	eline grease	400 ml	Printed on 24/02/2016 Page n. 2/12
		>		
Signal words:	Danger			
lazard statements:				
H222 H229 H315 H336 H411	Extremely flammable ae Pressurised container: n Causes skin irritation. May cause drowsiness o Toxic to aquatic life with	nay burst if heated. or dizziness.		
Precautionary stateme P210 P211 P251 P264 P280 P301+P310 P304+P340 P410+P412	Keep away from heat, ho Do not spray on an oper Do not pierce or burn, ev Wash thoroughly afte Wear protective gloves. IF SWALLOWED: imme IF INHALED: remove pe	n flame or other ign ven after use. er handling. diately call a POIS rson to fresh air ar	, open flames and other ignition s ition source. ON CENTER / doctor / nd keep comfortable for breathing peratures exceeding 50°C / 122°	ŀ
Contains:	NAPHTHA (PETROLEU	M), HYDROTREA	TED LIGHT	
Statements on the aspiration toxicity classification were no included in the label elements, based on section 1.3.3. of Anne to CLP.				
2.3. Other hazards.				
On the basis of availal	ole data, the product does not c	ontain any PBT or	vPvB in percentage greater than	0,1%.
SECTION 3. C	omposition/informati	on on ingred	lients.	
3.1. Substances.				
nformation not releval	nt.			
3.2. Mixtures.				
Contains:				
		Conc. %.	Classification 1272/2008	
Identification.	LEUM), HYDROTREATED	CONC. %.	(CLP).	

# GNOCCHI ECO- SPRAY S.R.L. Revision nr. 9 Dated 22/02/2016 Printed on 24/02/2016 Printed on 24/02/2016

Page n. 3/12

# G004 – Vaseline grease 400 ml

		Chronic 2 H411, Note P
EC. 265-151-9		
INDEX. 649-328-00-1		
Reg. no. 012119484561-34-xxxx		
BUTANE		
CAS. 106-97-8	22,5 - 24	Flam. Gas 1 H220, Note C U
EC. 203-448-7		
INDEX. 601-004-00-0		
PROPANE		
CAS. 74-98-6	22,5 - 24	Flam. Gas 1 H220, Note U
EC. 200-827-9		
INDEX. 601-003-00-5		

Note: Upper limit is not included into the range.

The full wording of hazard (H) phrases is given in section 16 of the sheet.

## **SECTION 4. First aid measures.**

## 4.1. Description of first aid measures.

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately. INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

## 4.2. Most important symptoms and effects, both acute and delayed.

For symptoms and effects caused by the contained substances, see chap. 11.

## 4.3. Indication of any immediate medical attention and special treatment needed.

Information not available.

# **SECTION 5. Firefighting measures.**

## 5.1. Extinguishing media.

SUITABLE EXTINGUISHING EQUIPMENT The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray. UNSUITABLE EXTINGUISHING EQUIPMENT None in particular.

5.2. Special hazards arising from the substance or mixture.

Revision nr. 9

Page n. 4/12

## G004 – Vaseline grease 400 ml

Dated 22/02/2016

Printed on 24/02/2016

## HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

If overheated, aerosol cans can deform, explode and be propelled considerable distances. Put a protective helmet on before approaching the fire. Do not breathe combustion products.

#### 5.3. Advice for firefighters.

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

## **SECTION 6.** Accidental release measures.

#### 6.1. Personal precautions, protective equipment and emergency procedures.

Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site. Send away individuals who are not suitably equipped. Wear protective gloves / protective clothing / eye protection / face protection.

#### 6.2. Environmental precautions.

Do not disperse in the environment.

#### 6.3. Methods and material for containment and cleaning up.

Use inert absorbent material to soak up leaked product. Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

#### 6.4. Reference to other sections.

Any information on personal protection and disposal is given in sections 8 and 13.

## **SECTION 7. Handling and storage.**

#### 7.1. Precautions for safe handling.

Avoid bunching of electrostatic charges. Do not spray on flames or incandescent bodies. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Do not eat, drink or smoke during use. Do not breathe spray.

#### 7.2. Conditions for safe storage, including any incompatibilities.

Store in a place where adequate ventilation is ensured, away from direct sunlight at a temperature below 50°C/122°F, away from any combustion sources.

<b>GNOCCHI ECO- S</b>	PRAY S.R.L.
-----------------------	-------------

Revision nr. 9

G004 – Vaseline grease 400 ml

Dated 22/02/2016

Printed on 24/02/2016 Page n. 5/12

7.3. Specific end use(s).

Information not available.

# **SECTION 8. Exposure controls/personal protection.**

## 8.1. Control parameters.

Regulatory References:

DEU	Deutschland	MAK-und BAT-Werte-Liste 2012
ESP	España	INSHT - Límites de exposición profesional para agentes químicos en
		España 2015
FRA	France	JORF n°0109 du 10 mai 2012 page 8773 texte n° 102
GRB	United Kingdom	EH40/2005 Workplace exposure limits
POL	Polska	ROZPORZĄDZENIE MINISTRA PRACY I POLITYKI SPOŁECZNEJ z dnia 16 grudnia 2011r
EU	OEL EU	Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC.
	TLV-ACGIH	ACGIH 2014

NAPHTHA (PETROLEUM), Threshold Limit Value.	HYDROTREAT	ED LIGHT						
Type	Country	TWA/8h		STEL/15min				
		mg/m3	ppm	mg/m3	ppm			
OEL	EU			72				
Health - Derived no-effect	level - DNEL / D Effects on consumers.	MEL			Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral.	1301 mg/kg/d	1301 mg/kg/d				,		
Inhalation.			1137 mg/m3	1137 mg/m3			5306 mg/m3	5306 mg/m3
Skin.	1377 mg/kg/d	1377 mg/kg/d					13964 mg/kg/d	13964 mg/kg/d
PROPANE								
Threshold Limit Value. Type	Country	TWA/8h		STEL/15min				
	,	mg/m3	ppm	mg/m3	ppm			
AGW	DEU	1800	1000	7200	4000			
MAK	DEU	1800	1000	7200	4000			
NDS	POL	1800						
TLV-ACGIH			1000					
BUTANE								
Threshold Limit Value. Type	Country	TWA/8h		STEL/15min				
		mg/m3	ppm	mg/m3	ppm			
AGW	DEU	2400	1000	9600	4000			
MAK	DEU	2400	1000	9600	4000			

## Revision nr. 9 Dated 22/02/2016

## G004 – Vaseline grease 400 ml

Printed on 24/02/2016

Page n. 6/12

VLA	ESP		800		
VLEP	FRA	1900	800		
WEL	GRB	1450	600	1810	750
NDS	POL	1900		3000	
TLV-ACGIH				2377	1000

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

#### 8.2. Exposure controls.

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION None required.

#### SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

#### EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

#### RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, a mask with a type AX filter combined with a type P filter should be worn (see standard EN 14387). Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

ENVIRONMENTAL EXPOSURE CONTROLS.

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

# **SECTION 9.** Physical and chemical properties.

## 9.1. Information on basic physical and chemical properties.

# G004 – Vaseline grease 400 ml

Revision nr. 9

Dated 22/02/2016

Printed on 24/02/2016 Page n. 7/12

Flammability of solids and gases Lower inflammability limit. Upper inflammability limit.	Not available. Not available. Not available.
Lower explosive limit.	Not available.
Upper explosive limit.	Not available.
Vapour pressure.	Not available.
Vapour density	Not available.
Relative density.	Not available.
Solubility	Not available.
Partition coefficient: n-octanol/water	Not available.
Auto-ignition temperature.	Not available.
Decomposition temperature.	Not available.
Viscosity	Not available.
Explosive properties	Not available.
Oxidising properties	Not available.
9.2. Other information.	
	79.00.0/

VOC (Directive 2010/75/EC) :	78,00 %
VOC (volatile carbon) :	64,65 %

## **SECTION 10. Stability and reactivity.**

#### 10.1. Reactivity.

There are no particular risks of reaction with other substances in normal conditions of use.

## 10.2. Chemical stability.

The product is stable in normal conditions of use and storage.

#### 10.3. Possibility of hazardous reactions.

No hazardous reactions are foreseeable in normal conditions of use and storage.

10.4. Conditions to avoid.

Avoid overheating.

#### 10.5. Incompatible materials.

Strong reducing or oxidising agents, strong acids or alkalis, hot material.

## 10.6. Hazardous decomposition products.

Information not available.

## **SECTION 11. Toxicological information.**

Revision nr. 9

# G004 – Vaseline grease 400 ml

Dated 22/02/2016 Printed on 24/02/2016

Page n. 8/12

## 11.1. Information on toxicological effects.

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification. It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

The introduction of even small quantities of this liquid into the respiratory system in case of ingestion or vomit may cause bronchopneumonia and pulmonary edema.

Acute effects: contact with skin may cause: irritation, erythema, edema, dryness and chapped skin. Ingestion may cause health disorders, including stomach pain and sting, nausea and sickness.

This product contains highly volatile substances, which may cause serious depression of the central nervous system (CNS) and have negative effects, such as drowsiness, dizziness, slow reflexes, narcosis.

## **SECTION 12. Ecological information.**

This product is dangerous for the environment and is toxic for aquatic organisms. In the long term, it have negative effects on acquatic environment. **12.1. Toxicity.** 

Information not available.

## 12.2. Persistence and degradability.

BUTANE Solubility in water.	mg/l 0,1 - 100
Rapidly biodegradable.	
PROPANE	
Solubility in water.	mg/l 0,1 - 100
Rapidly biodegradable.	-
NAPHTHA (PETROLEUM), HYDROTREATED LIGHT Rapidly biodegradable.	
12.3. Bioaccumulative potential.	
BUTANE	
	1,09
BUTANE Partition coefficient: n-	1,09
BUTANE Partition coefficient: n- octanol/water.	1,09 1,09
BUTANE Partition coefficient: n- octanol/water. PROPANE Partition coefficient: n-	

Revision nr. 9 Dated 22/02/2016

## G004 – Vaseline grease 400 ml

Printed on 24/02/2016

Page n. 9/12

HYDROTREATED LIGHT Partition coefficient: 1,78 soil/water.

12.5. Results of PBT and vPvB assessment.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects.

Information not available.

# **SECTION 13. Disposal considerations.**

#### 13.1. Waste treatment methods.

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

## **SECTION 14. Transport information.**

#### 14.1. UN number.

ADR / RID, IMDG, 1950 IATA:

#### 14.2. UN proper shipping name.

ADR / RID:	AEROSOLS,
IMDG:	FLAMMABLE AEROSOLS
INDO.	(NAPHTHA
	(PETROLEUM),
	HYDROTREATE
	D LIGHT)
IATA:	AEROSÓLS,
	FLAMMABLE

#### 14.3. Transport hazard class(es).

ADR / RID:	Class: 2	Label: 2.1
IMDG:	Class: 2	Label: 2.1
IATA:	Class: 2	Label: 2.1



#### 14.4. Packing group.

GNOCCHI ECO- SPRAY S.R.L. G004 – Vaseline grease 400 ml			Revision nr. 9 Dated 22/02/2016	
			Printed on 24/02/2016 Page n. 10/12	
ADR / RID, IMD IATA:	IG, -			
14.5. Environme	ntal hazards.			
ADR / RID:	Environmentally Hazardous.			
IMDG:	Marine Pollutant.			
IATA:	NO		$\checkmark$	
For Air transport,	environmentally hazardou	is mark is only mandatory for UN 3077 a	and UN 3082.	
14.6. Special pre	ecautions for user.			
ADR / RID:		HIN - Kemler:	Limited Quantities: 1 L	Tunnel restriction code: (D)
		Special Provision: -	-	
IMDG:		EMS: F-D, S-U	Limited Quantities: 1	
IATA:		Cargo:	L Maximum quantity: 150 Kg	Packaging instructions: 203
		Pass.:	Maximum quantity: 75 Kg	Packaging instructions: 203
		Special Instructions:	A145, A167, A802	200
14.7. Transport i	n bulk according to Anr	ex II of MARPOL73/78 and the IBC Co	ode.	
Information not re	levant.			
<b>SECTION 1</b>	15. Regulatory inf	ormation.		
15.1. Safety, he	ealth and environmental	regulations/legislation specific for th	e substance or mixture.	
Seveso categor	<u>y.</u> 8			
Restrictions relati	ng to the product or conta	ined substances pursuant to Annex XVI	I to EC Regulation 1907/2006.	
Product.	-			
Point.	40	)		
<u>Substances in Ca</u>	ndidate List (Art. 59 REA	<u>CH).</u>		
None.				
Substances subje	ect to authorisarion (Annex	XIV REACH).		
None.				
Substances subje	ect to exportation reporting	pursuant to (EC) Reg. 649/2012:		
_	-			

## G004 – Vaseline grease 400 ml

Revision nr. 9

Page n. 11/12

Dated 22/02/2016

## Printed on 24/02/2016

None.

Substances subject to the Rotterdam Convention:

None.

Substances subject to the Stockholm Convention:

None

Healthcare controls.

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

#### 15.2. Chemical safety assessment.

No chemical safety assessment has been processed for the mixture and the substances it contains.

# **SECTION 16. Other information.**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Gas 1	Flammable gas, category 1
Aerosol 1	Aerosol, category 1
Aerosol 3	Aerosol, category 3
Flam. Liq. 2	Flammable liquid, category 2
Asp. Tox. 1	Aspiration hazard, category 1
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic toxicity, category 2
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H229	Pressurised container: may burst if heated.
H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road

CAS NUMBER: Chemical Abstract Service Number

CE50: Effective concentration (required to induce a 50% effect)

CE NUMBER: Identifier in ESIS (European archive of existing substances)

CLP: EC Regulation 1272/2008 DNEL: Derived No Effect Level

EmS: Emergency Schedule

GHS: Globally Harmonized System of classification and labeling of chemicals

IATA DGR: International Air Transport Association Dangerous Goods Regulation

- IC50: Immobilization Concentration 50%

Revision nr. 9

## G004 – Vaseline grease 400 ml

Dated 22/02/2016

Printed on 24/02/2016 Page n. 12/12

- IMDG: International Maritime Code for dangerous goods
  - IMO: International Maritime Organization
  - INDEX NUMBER: Identifier in Annex VI of CLP
  - LC50: Lethal Concentration 50%
  - LD50: Lethal dose 50%
  - **OEL: Occupational Exposure Level**
  - PBT: Persistent bioaccumulative and toxic as REACH Regulation
  - PEC: Predicted environmental Concentration
  - PEL: Predicted exposure level
  - PNEC: Predicted no effect concentration
  - REACH: EC Regulation 1907/2006
  - RID: Regulation concerning the international transport of dangerous goods by train
  - TLV: Threshold Limit Value
  - TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
  - TWA STEL: Short-term exposure limit
  - TWA: Time-weighted average exposure limit
  - VOC: Volatile organic Compounds
  - vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
  - WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

- 1. Regulation (EU) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EU) 1272/2008 (CLP) of the European Parliament
- Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament 3.
- 4. Regulation (EU) 2015/830 of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- ECHA website
- Note for users.

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses. Provide appointed staff with adequate training on how to use chemical products.

Changes to previous review:

The following sections were modified:

02 / 03 / 08 / 09 / 11 / 12 / 15 / 16.