



Spray Silicone 400 ml (OL103)

This spray has a high lubricant and protective power, and it's ideal for all main materials. This product is water repellent and it prevents accumulation of electrostatic charge.



HOW TO USE: shake and spray directly on the surface from a distance of 15-25 cm. The product could be also be used with a straw that is attached to the cap.

Quantity	400 ml
Barcode	EAN 13: 8034108890142
Box / Case	12 pz

SPRAY SILICONE – This spray is based on pure silicone oil that has anti-stick release agents. It lubricates and gives a good water repellency on treated materials preventing the accumulation of electrostatic charges. It works as a polishing and protective spray on plastic parts. It also protects seals from cracking, increasing tightness and durability.

Technical Specifications:

Aspect	Tin-Plate can containing under pressure fluid
Color	Colorless
Odour	Characteristic of solvent
Relative density	at 20°C 0,62 ÷ 0,66 g/ml
Flash point	Und. 0° C extremely flammable
Pressure at 20°C	4/6 bar
Silicone Viscosity	350 - 400 mm ² /s a 25°C
Auto-ignition temperature	>400°C (data per the dry residual)
Steam pressure	<0.01 kPa a 20°C
Freezing point	ca -50°C
Water solubility	Insoluble

MODALITY OF STORAGE

Before using: stock the product in a dry location and don't stock it with a temperature under 0°C and over 45°C, after the use, keep containers closed. In the original package, the product can be conserved for 24 months (warranty). The product doesn't expire.

After the first usage: conserve in a fresh and dry location, away from hot spring. Keep out of reach of children.

This information, even if reliable, must be considered only approximate. We are not responsible for the wrong use of the product, or the violation of any license. Before using, the users should verify the suitability of the product for its specific use.

BEFORE USE, CONSULT THE SAFETY DATA SHEET OF THE PRODUCT