Vaseline oil 5 L (OL110)

This is another amazing Ambro-Sol product. This vaseline oil is in the tank of 5 liters, and it's ideal for industrial uses. It's indicated for periodically lubrication and It's recommended for the lubrication of delicate mechanism.



Quantity	5 L
Barcode	EAN 13: 8034108893600
Pack	1 pz

VASELINE OIL – Pure vaseline oil particularly used for applications where periodic maintenance, cleaning, and lubrification are necessary. It is recommended for the lubrication of delicate mechanisms. Due to its special formulation it protects and lasts for long periods of time.

Technical Specifications

Aspect	Tank
Color	Coloress
Odour	Odourless
Relative density	at 15°C 850 ÷ 865 kg/m3 (ASTM D 1298)
Flash point	from 180 to 210°C (ASTM D 92)
Vapor pressure	hPa 20 C: < 0,01
Viscosity	at 40°C: from 13,0 to 20,5 mm2/s (ASTM D 445) at100°C: to 3,0 to 4,4 mm2/s (ASTM D 445)
Vapor thickness	> 2,0
Solubility	Negligible
Miscibility	100% in hydrocarbons and most organic solvents
Sliding point	max -12°C (ASTM D 97)
Initial boiling point	from 218 to 580°C
Self-ignition Temp.	from 325 to 355°C

MODALITY OF STORAGE

Before using: stock the product in a dry location and don't stock it with a temperature under 0°C and over 45°C, after the use, keep containers closed. In the original package, the product can be conserved for 24 months (warranty). The product doesn't expire.
After the first usage: conserve in a fresh and dry location, away from hot spring. Keep out of reach of children.

This information, even if reliable, must be considered only approximate. We are not responsible for the wrong use of the product, or the violation of any license. Before using, the users should verify the suitability of the product for its specific use.

BEFORE USE, CONSULT THE SAFETY DATA SHEET OF THE PRODUCT

NIROX s.r.o. Polianky 17 Bratislava 841 01, tel +421 949 000 149, mail: eshop@nirox.sk, web: www.nirox.sk

Ambro-Sol is a registered trademark – All rights reserved – Total or partial reproduction is prohibited.