Marine Unblocking (S153)

This spray is specifically created to be used on parts exposed to water. This product has a high hydro-repellent and protective power; for that, it's ideal in marine and nautical sectors.



Quantity	400 ml
Barcode	EAN 13: 8034108890210
Box / Case	12 pz

MARINE UNBLOCKING – A multipurpose product: it lubricates, protects, and releases. It is water-repellent and corrosion preventive. Excellent lubricant, able to penetrate rusted bolts, fittings, chains, etc, in depth and release them. t protects parts subject to exposed water-pins, levers, and outboard motor parts. It meets the nautical market requirements and thanks to its high waterproofing/water-repellent capacities it's ideal for maintenance on any machine part.

HOW TO USE: Shake well before use. Spray the product on the part to treated, leave for a few minutes, in the case of rusted parts proceed with the unlocking. In presence of more resistant deposits repeat the operation. The product can be also be sprayed with the straw attached to the cap. PRECAUTIONS: Do not apply to equipment in tension. Do not apply to materials overheated**.**

Technical Specifications:

Aspect	Tin-Plate can containing under pressure fluid
Color	Light brown
Odour	Characteristic of solvent
Relative density	at 20°C 0,66 ÷ 0,70 g/ml
Flash point	Und. 0° C
Pressure at 20°C	4/6 bar
Melting/freezing point	< - 66°C (liquid base)
Boiling point	176°C circa (liquid base)
Vapor tension	> 6 bar (20°C)
Viscosity	< 3 cSt - 12 cSt 40°C (oily base)
Solubility	Insoluble in water
Operating Temp.	-50°C / +130 °C c.a.
2nd Flash point	+40 °C (liquid base)

MODALITY OF STORAGE

Before using: stock the product in a dry location and don't stock it with a temperature under 0°C and over 45°C, after the use, keep containers closed. In the original package, the product can be conserved for 24 months (warranty). The product doesn't expire.
After the first usage: conserve in a fresh and dry location, away from hot spring. Keep out of reach of children.

This information, even if reliable, must be considered only approximate. We are not responsible for the wrong use of the product, or the violation of any license. Before using, the users should verify the suitability of the product for its specific use.

BEFORE USE, CONSULT THE SAFETY DATA SHEET OF THE PRODUCT

NIROX s.r.o. Polianky 17 Bratislava 841 01, tel +421 949 000 149, mail: eshop@nirox.sk, web: www.nirox.sk

Ambro-Sol is a registered trademark – All rights reserved – Total or partial reproduction is prohibited.