Foamy Cable Sliding (S156)

This spray is ideal for electric contacts and cables: it removes friction and at the same time it doesn't harm materials, protects, and lubricates. This product is ideal in particular for electricians.



Quantity	400 ml
Barcode	EAN 13: 8034108891477
Box / Case	12 pz

FOAMY CABLE SLIDING – It eliminates friction and makes rubber and plastic electric cables easy to slide. It does not damage synthetic cable insulation. It proves to be an excellent protector that slows down natural ageing processes.

HOW TO USE: Shake Well before use. Spray the foam directly on the cables or inside the cable tunnel. The product can be also be sprayed with the straw attached to the cap.

Technical Specifications:

Aspect	Tin-Plate can containing under pressure fluid
Color	White
Odour	Odouless
Relative density	at 20°C 0,87 ÷ 0,91 g/ml
Flash point	Und.0° C extremely flammable
Pressure at 20°C	4/6 bar
viscosity	1-100 cps (25°C) (liquid base)
Density active base	Ca. 1,0 g/cm3
Water solubility	100%
Boiling point	Ca. 100 °C (liquid base)
PH	7 - 8,5 (liquid base)

MODALITY OF STORAGE

Before using: stock the product in a dry location and don't stock it with a temperature under 5°C and over 45°C, after the use, keep containers closed. In the original package, the product can be conserved for 24 months (warranty). The product doesn't expire.

After the first usage: conserve in a fresh and dry location, away from hot spring. Keep out of reach of children.

This information, even if reliable, must be considered only approximate. We are not responsible for the wrong use of the product, or the violation of any license. Before using, the users should verify the suitability of the product for its specific use.

BEFORE USE, CONSULT THE SAFETY DATA SHEET OF THE PRODUCT

NIROX s.r.o. Polianky 17 Bratislava 841 01, tel +421 949 000 149, mail: eshop@nirox.sk, web: www.nirox.sk

Ambro-Sol is a registered trademark – All rights reserved – Total or partial reproduction is prohibited.