



Graffiti Remover 400 ml (I256/GRAFF)

Graffiti Remover from the Ambro-Sol line helps to counteract vandalism by eliminating any kind of paint from walls, bricks and many other surfaces.



Quantity	400 ml
Barcode	8034108896410
Box / Case	12 pz

GRAFFITI REMOVER – It quickly removes all types of paint from metal and wood surfaces. It removes paint from walls and then prepares the worked part for new treatment. Caution: It may have damaging results on some pre-painted surface.

Technical Specifications:

Aspect	Spray can, containing pressurized liquid
Color	Transparent
Odor	Typical of solvent
Relative density	at 20°C 0,74 ÷ 0,78 g/ml
Flash Point	Und. 0° C extremely flammable
Pressure at 20°C	4/6 bar
Initial boiling point	> 30°C/ 86 °F (dry residual)
Dynamic viscosity	120,0 cp – 250,0 cp IST 524 (dry residual)
Solubility	Insoluble in water
Dry residual	1,2 % - 2,2 % (dry residual)
Exempt from chlorinated solvents	DMC
Vapor density	> 1 (dry residual)
Observations	May damage some prepainted surfaces For internal and external use.

HOW TO USE: Shake well before use for at least 1 minute. It is also suggested to occasionally shake the can even during use. Test on a less visible area. Apply an abundant layer of graffiti removal. Wait for the product to penetrate completely, then remove it with a clean cloth. High thixotropic even for vertical surface applications. Avoid using on plastic materials, hot surfaces or surfaces exposed to the sun.

MODALITY OF STORAGE

Before using: stock the product in a dry location and don't stock it with a temperature under 0°C and over 45°C, after the use, keep containers closed. In the original package, the product can be conserved for 24 months (warranty). The product doesn't expire.

After the first usage: conserve in a fresh and dry location, away from hot spring. Keep out of reach of children.

This information, even if reliable, must be considered only approximate. We are not responsible for the wrong use of the product, or the violation of any license. Before using, the users should verify the suitability of the product for its specific use.

BEFORE USE, CONSULT THE SAFETY DATA SHEET OF THE PRODUCT