

AMBRO-SOL[®]
Your Factory of Aerosol

SPRAY



Surface treatment enamel:

This paint is designed to be used as the base coat for a finishing enamels. It provides a strong base to ensure the perfect adhesion of the enamel spray on difficult surfaces such as plastics and metals. It protects metal surfaces from rust. On cars it covers small imperfections and scratches.

Available in six formats:

- V400STUCCO (white putty) – 400 ml spray can
- V400PRIMER2/ECO (eco plastic primer) – 400 ml spray can
- V400PAST.1/ECO (eco grey antirust) – 400 ml spray can
- V400PAST.1 (grey antirust) – 400 ml spray can
- V400PAST.9 (red antirust) – 400 ml spray can
- V400PAST.10 (white antirust) – 400 ml spray can

Technical Specifications:

Quantity	400 ml
Box / Case	6 Pz.
Aspect	Tin-Plate can containing under pressure fluid
Chemical nature	Acrylic
Colour	Various
Odour	Characteristic of solvent
Relative density at 20°C	0,71 ± 0,75 g/ml
Flash point	Und. 0° C extremely flammable
Writes on spray bottom	Barcode, Batch date, product name
Pressure	at 20°C 5,5 ± 0,5 bar
Pressure	at 50°C 8,0 ± 0,5 bar
Viscosity Ford cup	from 10" to 15"
Dry residual in spray	from 12% to 15%
Gloss	From 7 to 80 Gloss (Glossmeter angle 60°)
Thickness 1 coat	13-24 Micron
Drying time T=20°C:	Out dust: 15-30 minutes Dry to touch: 15-30 minutes Dry in full depth: 22 hours Overcoating Interval: 22/48 hours
Security cap child-proof patented and registered	
Token and ring with color reference	
Check the color and/or product type on the cap and/or on the bottom of the can.	