

AMBRO-SOL[®]

Your Factory of Aerosol

SPRAY



Stain cover:

This is a formulation that gives high hiding power after just one coat to completely eliminate any stain at all by penetrating deep below the surface and then creating a seal for the prevention of new stains. Suitable for all stains caused by smoke on walls, mildew, and dirt in general. The STAIN COVER covers any stain when applied evenly over the area to be treated. The removal of particularly "resistant" stains may require repeated application of product always from a distance of 20-30 cm, paying attention to avoid runs. The product dries in 5-8 minutes if applied at a temperature of 20°C.

Available in one format:

- V500COPRI – 500 ml spray can

Technical Specifications:

Quantity	500 ml
Box / Case	12 Pcs
Aspect	Tin-Plate can containing under pressure fluid
Chemical nature	Quick drying acrylic paints
Colour	White
Odour	Characteristic of solvent
Relative density at 20°C	0,77 ÷ 0,81 g/ml Primer e Antirust
Flash point	Und. 0° C extremely flammable
Writing on spray bottom	Barcode, Batch date, product name
Pressure	at 20°C 5,5 ± 0,5 bar
Viscosity Ford cup	from 13" to 18"
Dry residual in spray	46% (on dry film)
Gloss	From 5 to 10 Gloss (Glossmeter angle 60°)
Thickness 1 coat	13-24 Micron
Thickness 3 coats	36-54 Micron
Resistance temperature	-10°C / +130°C (Peak 150° C)
Drying time t=20°:	Out dust: 8-10 minutes Dry to touch: 30 minutes Dry in full depth: 22 hours Overcoating Interval: 22/48 hours
It is possible to have different type of dispenser for various effects and employ	