





Bright Zinc:

This is a cold galvanizer with high molecular weight. It chemically solidifies producing a long lasting metal coating. It protects all metal surfaces from oxidation. It forms a resistant layer which can be painted or left as a final protection. It is ideal for retouching, finishing, and repairing galvanized parts where a bright grey coat is required.

Available in one format:

- Z355 – 400 ml spray can

Technical Specifications:

rediffical openioations.	
Quantity	400ml
Box / Case	12 pcs
Barcode	EAN 13 8034108892276
Aspect	Tin-Plate can containing under pressure fluid
Physical state	Pigmented liquid in aerosol
Flash point	Und. 0° C extremely flammable
Pressure	at 20°C 5,5 bar
Relative density	at 20°C 0,71 ÷ 0,75 g/ml
Propellant	LPG
Chemical nature	Synthetic resin with inhibiting pigment of
	corrosion based on zinc dust
Colour	Inox Steel / light grey
Powder purity Zn	> 98%
Odour	Characteristic of solvent
% Metal in the dry film	53 %
% Zinc in the dry film	3 %
Resistance Temp.	300 °C (peak 350 °C)
Yield	2/3 mq2
Drying times = 20°	Out dust: 10'
	Dry to touch: 20'
	Dry in depth: 6 hour
	Overpainted after 12 hours