





Pure Zinc EP:

This is a cold galvanizer with high molecular weight. It chemically solidifies producing a long-lasting metal coating. It protects all metal surfaces from oxidation. It forms a resistant layer which can be painted or left as a final protection. It offers exceptional resistance to weathering in difficult conditions. It is ideal for retouching, finishing, and repairing galvanized parts.

Available in two formats:

- Z359 400 ml spray can
- Z356 1lt can

Technical Specifications:

Quantity	400 ml
Barcode	EAN 13: 8034108893785
Box / Case	12 pz
Aspect	Tin-Plate can containing under pressure fluid
Temperature resistance	80 °C
Color	Medium grey
Odour	Characteristic of solvent
Relative density	at 20°C 0,98 ÷ 1,02 g/ml
Propellent	DME
Physical state	Pigmented liquid in aerosol
Flash point	Und.0° C extremely flammable
Chemical nature	Resin with inhibiting pigment of base
	corrosion of Dust of zinc and of aluminium
Pressure at 20°C	5 bar
Pureness zinc dust	>98%
% Metal in the product	33 %
% Zinc in the product	30 %
Cylinder yield	2/3 sqm
Drying times (at 20 °C)	Out of dust: 20 minutes
	Dry on touch: 45 minutes
	Dry on depth: from 12 to 24 hours
	Overcoated after 24 hours